

ENTEL 300 DOOR ENTRY SYSTEM

Entel 300 functional door entry systems are suitable for low rise buildings with up to 20 dwellings and 2 entrance panels.



Entel 300 Si Functional Door Panel Features;

- ⚡ Vandal resistant 12 swg stainless steel fascia
- ⚡ Vandal resistant 20 mm stainless steel buttons
- ⚡ Flush galvanized backbox & stainless steel bezel
- ⚡ Engraved buttons (flat number/trade) max 15 per panel
- ⚡ Engraved operating instructions
- ⚡ Engraved high visibility yellow rings around buttons
- ⚡ Facility for PAC proximity token reader
- ⚡ High quality speech with anti-feedback circuit
- ⚡ Audible reassurance tones (calling/engaged/door open)
- ⚡ Facility for a press to exit button and door status contact
- ⚡ Link selectable fail safe or fail secure lock options
- ⚡ Optional 2 line text intelligent LCD display
- ⚡ Optional coded access facility (using digital door panel)
- ⚡ Optional surface/flush stainless steel cowlings

Entel 300 Controller Features:

- ⚡ Housed in an IP65 lockable enclosure
- ⚡ RAL 7035 stove enameled finish
- ⚡ Dimensions: 400x300x150mm
- ⚡ Integral switched/fused mains spur
- ⚡ Integral 13.8V DC 4A power supply unit
- ⚡ 8 fully isolated output channels as standard
- ⚡ Plug-in 6 channel expander boards (max 2)
- ⚡ 1 or 2 door panels as standard
- ⚡ Compatible with functional or digital door panels
- ⚡ Fully onsite programmable
- ⚡ Integral multifunction LCD display
- ⚡ Real time clock with auto-BST adjustment
- ⚡ Fault monitoring & status indication
- ⚡ Optional battery standby



Entel 300 Telephone Handset Features;

- ⚡ Modern design in white ABS
- ⚡ Single multifunction pushbutton (lock release/privacy)
- ⚡ Single multifunction LED indicator
- ⚡ 3 user selectable ring tones
- ⚡ Full privacy of speech
- ⚡ Onsite programmable privacy (on/off or timed)
- ⚡ Red privacy on LED indication
- ⚡ Green door open LED indication
- ⚡ Door left open warning tone (can be disabled)
- ⚡ Simple 2 pair connection to controller
- ⚡ Optional second telephone per dwelling
- ⚡ Optional hard of hearing strobe light



Cowley Road, Blyth Riverside Business Park,
Blyth, Northumberland, NE24 5TF
Tel: 01670 352371
Fax: 01670 362807
Email: sales@tynetec.co.uk
Website: www.tynetec.co.uk